


PERFORMANCE TABLE

45 FOOT BOOM (14 METER) RECOMMENDED FOR 540 GX SERIES TRAVELERS		 <small>JANUARY 2008</small>			SPEED OF P.E. PIPE PULL IN METERS/HOUR SPEED OF P.E. PIPE PULL IN FEET/HOUR													
					10	15	20	25	30	40	50	60	70	80	90	100		
					33	50	66	82	98	131	164	197	230	262	295	328		
# OF DOUBLE CUT NOZZLES	NOZZLE CUT HEIGHT (MM)	BOOM PRESSURE (PSI)	BOOM FLOW (GPM)	SURFACE RANGE (FEET)	PRECIPITATION RATE IN INCHES													
18 + 2 END NOZZLES 7MM – RG4	5.0 TYPE: RG4	15	56	75	2.2	1.4	1.1	0.9	0.7	0.5	0.4	0.4	0.3	0.3	0.2	0.2		
		29	78	82	2.8	1.9	1.4	1.1	1.0	0.7	0.6	0.5	0.4	0.4	0.3	0.3		
		44	94	89	3.1	2.1	1.6	1.2	1.0	0.8	0.5	0.5	0.4	0.4	0.3	0.3		
Performance data has been obtained under ideal test conditions and may be adversely affected by wind, poor hydraulic entrance conditions or other factors. No representation regarding droplet condition, uniformity, application rate or suitability for a particular application is made herein.																		